

# Single-Axis Robot

## 6. KS Series

### 6.1 Features

- ◎ For use in clean room
- ◎ Stainless steel cover
- ◎ Already installed AC servo motor (optional)
- ◎ High repeatability  $\pm 0.02\text{mm}$
- ◎ Dustproof
- ◎ Different strokes available

### 6.2 Applications


- ◎ FPD industry
- ◎ Semiconductor
- ◎ Medical applications
- ◎ FPD glass transfer
- ◎ Inspection & testing equipment




## 6.3 KS Series

### Model Number for KS090

| KS090 | -10         | P                               | -0600            | A              | F0           | S1                                                                                                              | M101                                                                                                                 |
|-------|-------------|---------------------------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Lead        | Precision Grade                 | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       | 5mm<br>10mm | P:<br>Precision<br>C:<br>Normal |                  | A:<br>Standard | F0: Direct   | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M05□, K05□<br>M10□, K10□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |



| Effective stroke (mm) | L   | A   | M | N  | Weight (kg) | AC motor output                                                                                 | W                                                                                                                                                           | 100                  |      |     |
|-----------------------|-----|-----|---|----|-------------|-------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|------|-----|
|                       |     |     |   |    |             | Drive                                                                                           |                                                                                                                                                             | Ballscrew C7(normal) |      |     |
| 50                    | 346 | 150 | 0 | 4  | 3.38        | Lead                                                                                            | mm                                                                                                                                                          | 5                    | 10   |     |
| 100                   | 396 | 50  | 1 | 6  | 3.78        | Rated RPM                                                                                       | RPM                                                                                                                                                         | 3000                 | 3000 |     |
| 150                   | 446 | 100 | 1 | 6  | 4.18        | Max linear speed*                                                                               | mm/sec                                                                                                                                                      | 250                  | 500  |     |
| 200                   | 496 | 150 | 1 | 6  | 4.58        | Rated thrust                                                                                    | N                                                                                                                                                           | 280                  | 140  |     |
| 250                   | 546 | 50  | 2 | 8  | 4.98        | Repeatability                                                                                   | mm                                                                                                                                                          | ±0.02                |      |     |
| 300                   | 596 | 100 | 2 | 8  | 5.38        | Effective stroke                                                                                | mm                                                                                                                                                          | 50~600               |      |     |
| 350                   | 646 | 150 | 2 | 8  | 5.78        | Max load (H)                                                                                    | kg                                                                                                                                                          | 24                   | 12   |     |
| 400                   | 696 | 50  | 3 | 10 | 6.18        | <div></div> | Fyd                                                                                                                                                         | N                    | 50   | 50  |
| 450                   | 746 | 100 | 3 | 10 | 6.58        |                                                                                                 | Fzd                                                                                                                                                         | N                    | 240  | 120 |
| 500                   | 796 | 150 | 3 | 10 | 7.19        |                                                                                                 | Mxd                                                                                                                                                         | N-m                  | 5    | 4.5 |
| 550                   | 846 | 50  | 4 | 12 | 7.38        |                                                                                                 | Myd                                                                                                                                                         | N-m                  | 2.3  | 2.1 |
| 600                   | 896 | 100 | 4 | 12 | 7.78        |                                                                                                 | Mzd                                                                                                                                                         | N-m                  | 2.3  | 2.1 |
|                       |     |     |   |    |             | Rated dynamic load**                                                                            |                                                                                                                                                             |                      |      |     |
|                       |     |     |   |    |             | Permitted load condition***                                                                     | $\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1$ <p>Fy, Fz, Mx, My, Mz are working loads</p> |                      |      |     |

\* Vibration might occur when the effective stroke is longer than 650mm.


The maximum speed should be decreased by 15% for every 100mm of increased stroke.

\*\* The load condition is based on 10,000km operation.

\*\*\* If used on the vertical axis or in a special condition, please contact HIWIN.

## Model Number for KS100-FI

| KS100 | -20          | P                               | -800             | A              | FI           | S2                                                                                                              | M101                                                                                                                 |
|-------|--------------|---------------------------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Lead         | Precision Grade                 | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       | 10mm<br>20mm | P:<br>Precision<br>C:<br>Normal |                  | A:<br>Standard | FI: Internal | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M05□, K05□<br>M10□, K10□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |



| Effective stroke (mm) | L    | N | Weight (kg) | AC motor output             | W                                                                                                                                                           | 100                  |
|-----------------------|------|---|-------------|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
|                       |      |   |             | Drive                       |                                                                                                                                                             | Ballscrew C7(normal) |
| 200                   | 600  | 3 | 9.1         | Lead                        | mm                                                                                                                                                          | 5 10 20              |
| 300                   | 700  | 4 | 9.8         | Rated RPM                   | RPM                                                                                                                                                         | 3000 3000 3000       |
| 400                   | 800  | 4 | 10.5        | Max linear speed*           | mm/sec                                                                                                                                                      | 250 500 1000         |
| 500                   | 900  | 5 | 11.2        | Rated thrust                | N                                                                                                                                                           | 280 140 70           |
| 600                   | 1000 | 6 | 11.9        | Repeatability               | mm                                                                                                                                                          | ±0.02                |
| 700                   | 1100 | 6 | 12.6        | Effective stroke            | mm                                                                                                                                                          | 200~800              |
| 800                   | 1200 | 7 | 13.3        | Max load (H)                | kg                                                                                                                                                          | 8 6 3.5              |
|                       |      |   |             | Rated dynamic load**        | Fyd                                                                                                                                                         | N 20 20 20           |
|                       |      |   |             |                             | Fzd                                                                                                                                                         | N 80 60 35           |
|                       |      |   |             |                             | Mxd                                                                                                                                                         | N-m 1.1 1.2 1.1      |
|                       |      |   |             |                             | Myd                                                                                                                                                         | N-m 0.9 0.9 0.9      |
|                       |      |   |             |                             | Mzd                                                                                                                                                         | N-m 0.9 0.9 0.9      |
|                       |      |   |             | Permitted load condition*** | $\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1$ <p>Fy, Fz, Mx, My, Mz are working loads</p> |                      |

\* Vibration might occur when the effective stroke is longer than 650mm.


The maximum speed should be decreased by 15% for every 100mm of increased stroke.


\*\* The load condition is based on 10,000km operation.

\*\*\* If used on the vertical axis or in a special condition, please contact HIWIN.

## Model Number for KS100-FL

| KS100 | -20          | P                               | -800             | A              | FL           | S2                                                                                                              | M101                                                                                                                 |
|-------|--------------|---------------------------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Lead         | Precision Grade                 | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       | 10mm<br>20mm | P:<br>Precision<br>C:<br>Normal |                  | A:<br>Standard | FL: Left     | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M05□, K05□<br>M10□, K10□<br>Motor specification:<br>ref. catalof P.167<br>M:customer specified<br>None:Without Motor |



| Effective stroke (mm) | L    | N | Weight (kg) | AC motor output                                                                                | W                                                                                                                                                                                                                                                       | 100                   |      |      |     |
|-----------------------|------|---|-------------|------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|------|------|-----|
|                       |      |   |             | Drive                                                                                          |                                                                                                                                                                                                                                                         | Ball screw C7(normal) |      |      |     |
| 200                   | 504  | 2 | 6.0         | Lead                                                                                           | mm                                                                                                                                                                                                                                                      | 5                     | 10   | 20   |     |
| 300                   | 604  | 3 | 6.9         | Rated RPM                                                                                      | RPM                                                                                                                                                                                                                                                     | 3000                  | 3000 | 3000 |     |
| 400                   | 704  | 3 | 7.8         | Max linear speed*                                                                              | mm/sec                                                                                                                                                                                                                                                  | 250                   | 500  | 1000 |     |
| 500                   | 804  | 4 | 8.7         | Rated thrust                                                                                   | N                                                                                                                                                                                                                                                       | 280                   | 140  | 70   |     |
| 600                   | 904  | 5 | 9.6         | Repeatability                                                                                  | mm                                                                                                                                                                                                                                                      | ±0.02                 |      |      |     |
| 700                   | 1004 | 5 | 10.5        | Effective stroke                                                                               | mm                                                                                                                                                                                                                                                      | 200~800               |      |      |     |
| 800                   | 1104 | 6 | 11.4        | Max load (H)                                                                                   | kg                                                                                                                                                                                                                                                      | 8                     | 6    | 3.5  |     |
|                       |      |   |             | <div></div> | F <sub>yd</sub>                                                                                                                                                                                                                                         | N                     | 20   | 20   | 20  |
|                       |      |   |             |                                                                                                | F <sub>zd</sub>                                                                                                                                                                                                                                         | N                     | 80   | 60   | 35  |
|                       |      |   |             |                                                                                                | M <sub>xd</sub>                                                                                                                                                                                                                                         | N-m                   | 1.1  | 1.2  | 1.1 |
|                       |      |   |             |                                                                                                | M <sub>yd</sub>                                                                                                                                                                                                                                         | N-m                   | 0.9  | 0.9  | 0.9 |
|                       |      |   |             |                                                                                                | M <sub>zd</sub>                                                                                                                                                                                                                                         | N-m                   | 0.9  | 0.9  | 0.9 |
|                       |      |   |             |                                                                                                | <div><math display="block">\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1</math><p>F<sub>y</sub>, F<sub>z</sub>, M<sub>x</sub>, M<sub>y</sub>, M<sub>z</sub> are working loads</p></div> |                       |      |      |     |

\* Vibration might occur when the effective stroke is longer than 650mm.


The maximum speed should be decreased by 15% for every 100mm of increased stroke.

\*\* The load condition is based on 10,000km operation.


\*\*\* If used on the vertical axis or in a special condition, please contact HIWIN.

## Model Number for KS100-FR

| KS100 | -20          | P                               | -800             | A              | FR           | S2                                                                                                              | M101                                                                                                                 |
|-------|--------------|---------------------------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Lead         | Precision Grade                 | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       | 10mm<br>20mm | P:<br>Precision<br>C:<br>Normal |                  | A:<br>Standard | FR: Right    | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M05□, K05□<br>M10□, K10□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |




| Effective stroke (mm) | L    | N | Weight (kg) | AC motor output             | W      | 100                  |
|-----------------------|------|---|-------------|-----------------------------|--------|----------------------|
|                       |      |   |             | Drive                       |        | Ballscrew C7(normal) |
| 200                   | 504  | 2 | 6.0         | Lead                        | mm     | 5 10 20              |
| 300                   | 604  | 3 | 6.9         | Rated RPM                   | RPM    | 3000 3000 3000       |
| 400                   | 704  | 3 | 7.8         | Max linear speed*           | mm/sec | 250 500 1000         |
| 500                   | 804  | 4 | 8.7         | Rated thrust                | N      | 280 140 70           |
| 600                   | 904  | 5 | 9.6         | Repeatability               | mm     | ±0.02                |
| 700                   | 1004 | 5 | 10.5        | Effective stroke            | mm     | 200~800              |
| 800                   | 1104 | 6 | 11.4        | Max load (H)                | kg     | 8 6 3.5              |
|                       |      |   |             | Rated dynamic load**        |        |                      |
|                       |      |   |             | Permitted load condition*** |        |                      |



\* Vibration might occur when the effective stroke is longer than 650mm.  
The maximum speed should be decreased by 15% for every 100mm of increased stroke.  
\*\* The load condition is based on 10,000km operation.  
\*\*\* If used on the vertical axis or in a special condition, please contact HIWIN.


| KS100 | B           | -84              | C               | -3000            | A              | FL           | S2                                                                                                              | M101                                                                                                                 |
|-------|-------------|------------------|-----------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Timing Belt | Pulley Perimeter | Precision Grade | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       |             |                  | C:<br>Normal    |                  | A:<br>Standard | FL: Left     | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M05□, K05□<br>M10□, K10□<br>Motor specification:<br>ref. catalof P.167<br>M:customer specified<br>None:Without Motor |




\*\*For horizontal applications only. If used in a special condition, please contact HIWIN.

## Model Number for KS100B-FR

| KS100 | B           | -84              | C               | -3000            | A              | FR           | S2                                                                                                              | M101                                                                                                                 |
|-------|-------------|------------------|-----------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Timing Belt | Pulley Perimeter | Precision Grade | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       |             |                  | C:<br>Normal    |                  | A:<br>Standard | FR: Right    | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M05□, K05□<br>M10□, K10□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |



| Effective stroke (mm) | L    | N  | Weight [kg] | AC motor output            |                                                                                                                                                             | W   | 100         |     |
|-----------------------|------|----|-------------|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-------------|-----|
|                       |      |    |             | Drive                      |                                                                                                                                                             |     | Timing Belt |     |
| 200                   | 558  | 2  | 6.1         | Pulley Perimeter           | mm                                                                                                                                                          |     | 84          |     |
| 400                   | 758  | 4  | 7.6         | Pulley RPM                 | RPM                                                                                                                                                         |     | 1286        |     |
| 600                   | 958  | 5  | 9.1         | Max linear speed           | mm/sec                                                                                                                                                      |     | 1800        |     |
| 800                   | 1158 | 6  | 10.6        | Rated thrust               | N                                                                                                                                                           |     | 33          |     |
| 1000                  | 1358 | 8  | 12.1        | Repeatability              | mm                                                                                                                                                          |     | ±0.1        |     |
| 1200                  | 1558 | 9  | 13.6        | Effective stroke           | mm                                                                                                                                                          |     | 200~3000    |     |
| 1400                  | 1758 | 10 | 15.1        | Max load (H)               | kg                                                                                                                                                          |     | 3           |     |
| 1600                  | 1958 | 12 | 16.6        | Rated dynamic load*        |                                                                          | Fyd | N           | 20  |
| 1800                  | 2158 | 13 | 18.1        |                            |                                                                                                                                                             | Fzd | N           | 30  |
| 2000                  | 2358 | 14 | 19.6        |                            |                                                                                                                                                             | Mxd | N-m         | 1.2 |
| 2200                  | 2558 | 16 | 21.1        |                            |                                                                                                                                                             | Myd | N-m         | 1   |
| 2400                  | 2758 | 17 | 22.6        |                            |                                                                                                                                                             | Mzd | N-m         | 1   |
| 2600                  | 2958 | 18 | 24.1        | Permitted load condition** | $\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1$ <p>Fy, Fz, Mx, My, Mz are working loads</p> |     |             |     |
| 2800                  | 3158 | 20 | 25.6        |                            |                                                                                                                                                             |     |             |     |
| 3000                  | 3358 | 21 | 27.1        |                            |                                                                                                                                                             |     |             |     |


\*The load condition is based on 10,000km operation.


\*\*For horizontal applications only. If used in a special condition, please contact HIWIN.



## Model Number for KS140-FI

| KS140 | -20          | P                               | -1100            | A              | FI           | S2                                                                                                              | M201                                                                                                                 |
|-------|--------------|---------------------------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Lead         | Precision Grade                 | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       | 10mm<br>20mm | P:<br>Precision<br>C:<br>Normal |                  | A:<br>Standard | FI: Internal | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M20□, K20□<br>M40□, K40□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |



| Effective stroke (mm) | L    | N   | Weight (kg) | AC motor output                                                                                                                                                                                                                                                                                                                                                                                                                                        | W                                                                                                                                                                                                                  | 200                  |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
|-----------------------|------|-----|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|------|----|-----------------|---|-----|-----|-----------------|-----|----|----|-----------------|-----|----|----|-----------------|-----|----|----|--|--|--|
|                       |      |     |             | Drive                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                    | Ballscrew C7(normal) |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| 200                   | 700  | 3   | 13.5        | Lead                                                                                                                                                                                                                                                                                                                                                                                                                                                   | mm                                                                                                                                                                                                                 | 10                   | 20   |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| 300                   | 800  | 3   | 14.7        | Rated RPM                                                                                                                                                                                                                                                                                                                                                                                                                                              | RPM                                                                                                                                                                                                                | 3000                 | 3000 |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| 400                   | 900  | 4   | 15.9        | Max linear speed*                                                                                                                                                                                                                                                                                                                                                                                                                                      | mm/sec                                                                                                                                                                                                             | 500                  | 1000 |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| 500                   | 1000 | 4   | 17.1        | Rated thrust                                                                                                                                                                                                                                                                                                                                                                                                                                           | N                                                                                                                                                                                                                  | 280                  | 140  |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| 600                   | 1100 | 5   | 18.3        | Repeatability                                                                                                                                                                                                                                                                                                                                                                                                                                          | mm                                                                                                                                                                                                                 | ±0.02                |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| 700                   | 1200 | 5   | 19.5        | Effective stroke                                                                                                                                                                                                                                                                                                                                                                                                                                       | mm                                                                                                                                                                                                                 | 200~1100             |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| 800                   | 1300 | 6   | 20.7        | Max load (H)                                                                                                                                                                                                                                                                                                                                                                                                                                           | kg                                                                                                                                                                                                                 | 75                   | 35   |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| 900                   | 1400 | 6   | 21.9        | <div></div> <table><tr><td>F<sub>yd</sub></td><td>N</td><td>50</td><td>50</td></tr><tr><td>F<sub>zd</sub></td><td>N</td><td>750</td><td>350</td></tr><tr><td>M<sub>xd</sub></td><td>N-m</td><td>55</td><td>60</td></tr><tr><td>M<sub>yd</sub></td><td>N-m</td><td>47</td><td>51</td></tr><tr><td>M<sub>zd</sub></td><td>N-m</td><td>47</td><td>51</td></tr></table> | F <sub>yd</sub>                                                                                                                                                                                                    | N                    | 50   | 50 | F <sub>zd</sub> | N | 750 | 350 | M <sub>xd</sub> | N-m | 55 | 60 | M <sub>yd</sub> | N-m | 47 | 51 | M <sub>zd</sub> | N-m | 47 | 51 |  |  |  |
| F <sub>yd</sub>       | N    | 50  | 50          |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                    |                      |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| F <sub>zd</sub>       | N    | 750 | 350         |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                    |                      |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| M <sub>xd</sub>       | N-m  | 55  | 60          |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                    |                      |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| M <sub>yd</sub>       | N-m  | 47  | 51          |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                    |                      |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| M <sub>zd</sub>       | N-m  | 47  | 51          |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                    |                      |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| 1000                  | 1500 | 7   | 23.2        |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                    |                      |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
| 1100                  | 1600 | 7   | 24.4        |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                    |                      |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
|                       |      |     |             | Rated dynamic load**                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                    |                      |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |
|                       |      |     |             | Permitted load condition***                                                                                                                                                                                                                                                                                                                                                                                                                            | $\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1$ <p>F<sub>y</sub>, F<sub>z</sub>, M<sub>x</sub>, M<sub>y</sub>, M<sub>z</sub> are working loads</p> |                      |      |    |                 |   |     |     |                 |     |    |    |                 |     |    |    |                 |     |    |    |  |  |  |

\* Vibration might occur when the effective stroke is longer than 800mm.


The maximum speed should be decreased by 15% for every 100mm of increased stroke.


\*\* The load condition is based on 10,000km operation.

\*\*\* If used on the vertical axis or in a special condition, please contact HIWIN.

## Model Number for KS140-FL

| KS140 | -20          | P                               | -1100            | A              | FL           | S2                                                                                                              | M201                                                                                                                 |
|-------|--------------|---------------------------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Lead         | Precision Grade                 | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       | 10mm<br>20mm | P:<br>Precision<br>C:<br>Normal |                  | A:<br>Standard | FL: Left     | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M20□, K20□<br>M40□, K40□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |



| Effective stroke (mm) | L    | N | Weight (kg) | AC motor output                                                                                | W                                                                                                                                                           | 200                  |      |     |
|-----------------------|------|---|-------------|------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|------|-----|
|                       |      |   |             | Drive                                                                                          |                                                                                                                                                             | Ballscrew C7(normal) |      |     |
| 200                   | 514  | 1 | 11.5        | Lead                                                                                           | mm                                                                                                                                                          | 10                   | 20   |     |
| 300                   | 614  | 2 | 13.0        | Rated RPM                                                                                      | RPM                                                                                                                                                         | 3000                 | 3000 |     |
| 400                   | 714  | 2 | 14.5        | Max linear speed*                                                                              | mm/sec                                                                                                                                                      | 500                  | 1000 |     |
| 500                   | 814  | 3 | 16.0        | Rated thrust                                                                                   | N                                                                                                                                                           | 280                  | 140  |     |
| 600                   | 914  | 3 | 17.5        | Repeatability                                                                                  | mm                                                                                                                                                          | ±0.02                |      |     |
| 700                   | 1014 | 4 | 19.0        | Effective stroke                                                                               | mm                                                                                                                                                          | 200~1100             |      |     |
| 800                   | 1114 | 4 | 20.5        | Max load (H)                                                                                   | kg                                                                                                                                                          | 75                   | 35   |     |
| 900                   | 1214 | 5 | 22.0        | <div></div> | Fyd                                                                                                                                                         | N                    | 50   | 50  |
| 1000                  | 1314 | 5 | 23.5        |                                                                                                | Fzd                                                                                                                                                         | N                    | 750  | 350 |
| 1100                  | 1414 | 6 | 25.0        |                                                                                                | Mxd                                                                                                                                                         | N-m                  | 55   | 60  |
|                       |      |   |             |                                                                                                | Myd                                                                                                                                                         | N-m                  | 47   | 51  |
|                       |      |   |             |                                                                                                | Mzd                                                                                                                                                         | N-m                  | 47   | 51  |
|                       |      |   |             | Permitted load condition***                                                                    | $\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1$ <p>Fy, Fz, Mx, My, Mz are working loads</p> |                      |      |     |

\* Vibration might occur when the effective stroke is longer than 800mm.

The maximum speed should be decreased by 15% for every 100mm of increased stroke.


\*\* The load condition is based on 10,000km operation.


\*\*\* If used on the vertical axis or in a special condition, please contact HIWIN.



## Model Number for KS140B-FL

| KS140 | B           | -120             | C               | -3000            | A              | FL           | S2                                                                                                              | M201                                                                                                                 |
|-------|-------------|------------------|-----------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Timing Belt | Pulley Perimeter | Precision Grade | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       |             |                  | C:<br>Normal    |                  | A:<br>Standard | FL: Left     | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M20□, K20□<br>M40□, K40□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |




| Effective stroke (mm) | L    | N  | Weight (kg) | AC motor output                                                                                                                                                                                                                        | 200    |             |     |
|-----------------------|------|----|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|-------------|-----|
|                       |      |    |             | Drive                                                                                                                                                                                                                                  | W      | Timing Belt |     |
| 200                   | 639  | 2  | 10.4        | Pulley Perimeter                                                                                                                                                                                                                       | mm     | 120         |     |
| 400                   | 839  | 3  | 12.6        | Pulley RPM                                                                                                                                                                                                                             | RPM    | 900         |     |
| 600                   | 1039 | 4  | 14.8        | Max linear speed                                                                                                                                                                                                                       | mm/sec | 1800        |     |
| 800                   | 1239 | 5  | 17.0        | Rated thrust                                                                                                                                                                                                                           | N      | 67          |     |
| 1000                  | 1439 | 6  | 19.2        | Repeatability                                                                                                                                                                                                                          | mm     | ±0.1        |     |
| 1200                  | 1639 | 7  | 21.4        | Effective stroke                                                                                                                                                                                                                       | mm     | 200~3000    |     |
| 1400                  | 1839 | 8  | 23.6        | Max load (H)                                                                                                                                                                                                                           | kg     | 15          |     |
| 1600                  | 2039 | 9  | 25.8        | <div>Rated dynamic load*</div> <div></div>                                                                                                          | Fyd    | N           | 50  |
| 1800                  | 2239 | 10 | 28.0        |                                                                                                                                                                                                                                        | Fzd    | N           | 150 |
| 2000                  | 2439 | 11 | 30.2        |                                                                                                                                                                                                                                        | Mxd    | N-m         | 67  |
| 2200                  | 2639 | 12 | 32.4        |                                                                                                                                                                                                                                        | Myd    | N-m         | 53  |
| 2400                  | 2839 | 13 | 34.6        |                                                                                                                                                                                                                                        | Mzd    | N-m         | 53  |
| 2600                  | 3039 | 14 | 36.8        | <div>Permitted load condition**</div> <div><math display="block">\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1</math><p>Fy, Fz, Mx, My, Mz are working loads</p></div> |        |             |     |
| 2800                  | 3239 | 15 | 39.0        |                                                                                                                                                                                                                                        |        |             |     |
| 3000                  | 3439 | 16 | 41.2        |                                                                                                                                                                                                                                        |        |             |     |


\*The load condition is based on 10,000km operation.

\*\*For horizontal applications only. If used in a special condition, please contact HIWIN.

## Model Number for KS140B-FR

| KS140 | B           | -120             | C               | -3000            | A              | FR           | S2                                                                                                              | M201                                                                                                                 |
|-------|-------------|------------------|-----------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Timing Belt | Pulley Perimeter | Precision Grade | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       |             |                  | C:<br>Normal    |                  | A:<br>Standard | FR: Right    | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M20□, K20□<br>M40□, K40□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |




| Effective stroke (mm) | L    | N  | Weight (kg) | AC motor output                                                                                                                                                                                                                        | W      | 200         |     |
|-----------------------|------|----|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|-------------|-----|
|                       |      |    |             | Drive                                                                                                                                                                                                                                  |        | Timing Belt |     |
| 200                   | 639  | 2  | 10.4        | Pulley Perimeter                                                                                                                                                                                                                       | mm     | 120         |     |
| 400                   | 839  | 3  | 12.6        | Pulley RPM                                                                                                                                                                                                                             | RPM    | 900         |     |
| 600                   | 1039 | 4  | 14.8        | Max linear speed                                                                                                                                                                                                                       | mm/sec | 1800        |     |
| 800                   | 1239 | 5  | 17.0        | Rated thrust                                                                                                                                                                                                                           | N      | 67          |     |
| 1000                  | 1439 | 6  | 19.2        | Repeatability                                                                                                                                                                                                                          | mm     | ±0.1        |     |
| 1200                  | 1639 | 7  | 21.4        | Effective stroke                                                                                                                                                                                                                       | mm     | 200~3000    |     |
| 1400                  | 1839 | 8  | 23.6        | Max load (H)                                                                                                                                                                                                                           | kg     | 15          |     |
| 1600                  | 2039 | 9  | 25.8        | <div>Rated dynamic load*</div> <div></div>                                                                                                          | Fyd    | N           | 50  |
| 1800                  | 2239 | 10 | 28.0        |                                                                                                                                                                                                                                        | Fzd    | N           | 150 |
| 2000                  | 2439 | 11 | 30.2        |                                                                                                                                                                                                                                        | Mxd    | N-m         | 67  |
| 2200                  | 2639 | 12 | 32.4        |                                                                                                                                                                                                                                        | Myd    | N-m         | 53  |
| 2400                  | 2839 | 13 | 34.6        |                                                                                                                                                                                                                                        | Mzd    | N-m         | 53  |
| 2600                  | 3039 | 14 | 36.8        | <div>Permitted load condition**</div> <div><math display="block">\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1</math><p>Fy, Fz, Mx, My, Mz are working loads</p></div> |        |             |     |
| 2800                  | 3239 | 15 | 39.0        |                                                                                                                                                                                                                                        |        |             |     |
| 3000                  | 3439 | 16 | 41.2        |                                                                                                                                                                                                                                        |        |             |     |


\*The load condition is based on 10,000km operation.

\*\*For horizontal applications only. If used in a special condition, please contact HIWIN.

## Model Number for KS150-FI


| KS150 | -10            | P                               | -1250            | A              | FI           | S1                                                                                                              | M201                                                                                                                 |
|-------|----------------|---------------------------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Lead           | Precision Grade                 | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       | 10 mm<br>20 mm | P:<br>Precision<br>C:<br>Normal |                  | A:<br>Standard | FI: Internal | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M20□, K20□<br>M40□, K40□<br>Motor specification:<br>ref. catalof P.167<br>M:customer specified<br>None:Without Motor |




| Effective stroke (mm) | L    | A   | M | N  | Weight (kg) | AC motor output                                                                                | W                                                                                                                                                                                                                                                                                                                               | 200                  |      |     |  |
|-----------------------|------|-----|---|----|-------------|------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|------|-----|--|
| 150                   | 669  | 200 | 2 | 8  | 13.96       | Drive                                                                                          |                                                                                                                                                                                                                                                                                                                                 | Ballscrew C7(normal) |      |     |  |
| 200                   | 719  | 50  | 3 | 10 | 14.84       | Lead                                                                                           | mm                                                                                                                                                                                                                                                                                                                              | 10                   | 20   |     |  |
| 250                   | 769  | 100 | 3 | 10 | 15.72       | Rated RPM                                                                                      | RPM                                                                                                                                                                                                                                                                                                                             | 3000                 | 3000 |     |  |
| 300                   | 819  | 150 | 3 | 10 | 16.6        | Max linear speed*                                                                              | mm/sec                                                                                                                                                                                                                                                                                                                          | 500                  | 1000 |     |  |
| 350                   | 869  | 200 | 3 | 10 | 17.48       | Rated thrust                                                                                   | N                                                                                                                                                                                                                                                                                                                               | 280                  | 140  |     |  |
| 400                   | 919  | 50  | 4 | 12 | 18.36       | Repeatability                                                                                  | mm                                                                                                                                                                                                                                                                                                                              | ±0.02                |      |     |  |
| 450                   | 969  | 100 | 4 | 12 | 19.24       | Effective stroke                                                                               | mm                                                                                                                                                                                                                                                                                                                              | 150~1250             |      |     |  |
| 500                   | 1019 | 150 | 4 | 12 | 20.12       | Max load (H)                                                                                   | kg                                                                                                                                                                                                                                                                                                                              | 80                   | 40   |     |  |
| 550                   | 1069 | 200 | 4 | 12 | 21          | <div></div> | Fyd                                                                                                                                                                                                                                                                                                                             | N                    | 50   | 50  |  |
| 600                   | 1119 | 50  | 5 | 14 | 21.88       |                                                                                                | Fzd                                                                                                                                                                                                                                                                                                                             | N                    | 800  | 400 |  |
| 650                   | 1169 | 100 | 5 | 14 | 22.76       |                                                                                                | Mxd                                                                                                                                                                                                                                                                                                                             | N-m                  | 56   | 63  |  |
| 700                   | 1219 | 150 | 5 | 14 | 23.64       |                                                                                                | Myd                                                                                                                                                                                                                                                                                                                             | N-m                  | 49   | 53  |  |
| 750                   | 1269 | 200 | 5 | 14 | 24.52       |                                                                                                | Mzd                                                                                                                                                                                                                                                                                                                             | N-m                  | 49   | 53  |  |
| 800                   | 1319 | 50  | 6 | 16 | 25.4        | <div><p>Rated dynamic load**</p></div>                                                         | <div><math display="block">\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1</math><p>Fy, Fz, Mx, My, Mz are working loads</p></div>                                                                                                                                |                      |      |     |  |
| 850                   | 1369 | 100 | 6 | 16 | 26.28       |                                                                                                |                                                                                                                                                                                                                                                                                                                                 |                      |      |     |  |
| 900                   | 1419 | 150 | 6 | 16 | 27.16       |                                                                                                |                                                                                                                                                                                                                                                                                                                                 |                      |      |     |  |
| 950                   | 1469 | 200 | 6 | 16 | 28.04       |                                                                                                |                                                                                                                                                                                                                                                                                                                                 |                      |      |     |  |
| 1000                  | 1519 | 50  | 7 | 18 | 28.92       |                                                                                                |                                                                                                                                                                                                                                                                                                                                 |                      |      |     |  |
| 1050                  | 1569 | 100 | 7 | 18 | 29.8        | <div><p>Permitted load condition***</p></div>                                                  | <div><p>* Vibration might occur when the effective stroke is longer than 700mm.<br/>The maximum speed should be decreased by 15% for every 100mm of increased stroke.<br/>** The load condition is based on 10,000km operation.<br/>*** If used on the vertical axis or in a special condition, please contact HIWIN.</p></div> |                      |      |     |  |
| 1100                  | 1619 | 150 | 7 | 18 | 30.68       |                                                                                                |                                                                                                                                                                                                                                                                                                                                 |                      |      |     |  |
| 1150                  | 1669 | 200 | 7 | 18 | 31.56       |                                                                                                |                                                                                                                                                                                                                                                                                                                                 |                      |      |     |  |
| 1200                  | 1719 | 50  | 8 | 20 | 32.44       |                                                                                                |                                                                                                                                                                                                                                                                                                                                 |                      |      |     |  |
| 1250                  | 1769 | 100 | 8 | 20 | 33.32       |                                                                                                |                                                                                                                                                                                                                                                                                                                                 |                      |      |     |  |

## Model Number for KS180-FI

| KS180 | -20          | P                               | -1200            | A              | FI           | S2                                                                                                              | M401                                                                                                                 |
|-------|--------------|---------------------------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Lead         | Precision Grade                 | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       | 10mm<br>20mm | P:<br>Precision<br>C:<br>Normal |                  | A:<br>Standard | FI: Internal | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M20□, K20□<br>M40□, K40□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |



| Effective stroke (mm) | L    | N | Weight (kg) | AC motor output                                                                                | W                                                                                                                                                           | 400                  |      |     |
|-----------------------|------|---|-------------|------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|------|-----|
|                       |      |   |             | Drive                                                                                          |                                                                                                                                                             | Ballscrew C7(normal) |      |     |
| 200                   | 710  | 3 | 16.5        | Lead                                                                                           | mm                                                                                                                                                          | 10                   | 20   |     |
| 300                   | 810  | 3 | 18.1        | Rated RPM                                                                                      | RPM                                                                                                                                                         | 3000                 | 3000 |     |
| 400                   | 910  | 4 | 19.7        | Max linear speed*                                                                              | mm/sec                                                                                                                                                      | 500                  | 1000 |     |
| 500                   | 1010 | 4 | 21.3        | Rated thrust                                                                                   | N                                                                                                                                                           | 560                  | 280  |     |
| 600                   | 1110 | 5 | 22.9        | Repeatability                                                                                  | mm                                                                                                                                                          | ±0.02                |      |     |
| 700                   | 1210 | 5 | 24.4        | Effective stroke                                                                               | mm                                                                                                                                                          | 200~1200             |      |     |
| 800                   | 1310 | 6 | 26          | Max load (H)                                                                                   | kg                                                                                                                                                          | 110                  | 50   |     |
| 900                   | 1410 | 6 | 27.6        | <div></div> | Fyd                                                                                                                                                         | N                    | 50   | 50  |
| 1000                  | 1510 | 7 | 29.2        |                                                                                                | Fzd                                                                                                                                                         | N                    | 1100 | 500 |
| 1100                  | 1610 | 7 | 30.8        |                                                                                                | Mxd                                                                                                                                                         | N-m                  | 60   | 65  |
| 1200                  | 1710 | 8 | 32.3        |                                                                                                | Myd                                                                                                                                                         | N-m                  | 45   | 53  |
|                       |      |   |             |                                                                                                | Mzd                                                                                                                                                         | N-m                  | 45   | 53  |
|                       |      |   |             | Permitted load condition***                                                                    | $\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1$ <p>Fy, Fz, Mx, My, Mz are working loads</p> |                      |      |     |

\* Vibration might occur when the effective stroke is longer than 800mm.


The maximum speed should be decreased by 15% for every 100mm of increased stroke.

\*\* The load condition is based on 10,000km operation.

\*\*\* If used on the vertical axis or in a special condition, please contact HIWIN.

## Model Number for KS180-FL

| KS180 | -20          | P                               | -1200            | A              | FL           | S2                                                                                                              | M401                                                                                                                 |
|-------|--------------|---------------------------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Lead         | Precision Grade                 | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       | 10mm<br>20mm | P:<br>Precision<br>C:<br>Normal |                  | A:<br>Standard | FL: Left     | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M20□, K20□<br>M40□, K40□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |



| Effective stroke (mm) | L    | N | Weight (kg) | AC motor output             | W                                                                                                                                                                                                                    | 400                  |
|-----------------------|------|---|-------------|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
|                       |      |   |             | Drive                       |                                                                                                                                                                                                                      | Ballscrew C7(normal) |
| 200                   | 532  | 1 | 11.3        | Lead                        | mm                                                                                                                                                                                                                   | 10 20                |
| 300                   | 632  | 2 | 12.3        | Rated RPM                   | RPM                                                                                                                                                                                                                  | 3000 3000            |
| 400                   | 732  | 2 | 13.3        | Max linear speed*           | mm/sec                                                                                                                                                                                                               | 500 1000             |
| 500                   | 832  | 3 | 14.3        | Rated thrust                | N                                                                                                                                                                                                                    | 560 280              |
| 600                   | 932  | 3 | 15.3        | Repeatability               | mm                                                                                                                                                                                                                   | ±0.02                |
| 700                   | 1032 | 4 | 16.3        | Effective stroke            | mm                                                                                                                                                                                                                   | 200-1200             |
| 800                   | 1132 | 4 | 17.3        | Max load (H)                | kg                                                                                                                                                                                                                   | 110 50               |
| 900                   | 1232 | 5 | 18.3        | Rated dynamic load**        | F <sub>yd</sub>                                                                                                                                                                                                      | N 50 50              |
| 1000                  | 1332 | 5 | 19.3        |                             | F <sub>zd</sub>                                                                                                                                                                                                      | N 1100 500           |
| 1100                  | 1432 | 6 | 20.3        |                             | M <sub>xd</sub>                                                                                                                                                                                                      | N-m 60 65            |
| 1200                  | 1532 | 6 | 21.3        |                             | M <sub>yd</sub>                                                                                                                                                                                                      | N-m 45 53            |
|                       |      |   |             |                             | M <sub>zd</sub>                                                                                                                                                                                                      | N-m 45 53            |
|                       |      |   |             | Permitted load condition*** | $\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1$ F <sub>y</sub> , F <sub>z</sub> , M <sub>x</sub> , M <sub>y</sub> , M <sub>z</sub> are working loads |                      |

\* Vibration might occur when the effective stroke is longer than 800mm.


The maximum speed should be decreased by 15% for every 100mm of increased stroke.


\*\* The load condition is based on 10,000km operation.

\*\*\* If used on the vertical axis or in a special condition, please contact HIWIN.

## Model Number for KS180-FR

| KS180 | -20          | P                               | -1200            | A              | FR           | S2                                                                                                              | M401                                                                                                                 |
|-------|--------------|---------------------------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Lead         | Precision Grade                 | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       | 10mm<br>20mm | P:<br>Precision<br>C:<br>Normal |                  | A:<br>Standard | FR: Right    | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M20□, K20□<br>M40□, K40□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |



| Effective stroke (mm) | L    | N | Weight (kg) | AC motor output                                                                                                         | W                                                                                                                                                           | 400                   |      |     |
|-----------------------|------|---|-------------|-------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|------|-----|
|                       |      |   |             | Drive                                                                                                                   |                                                                                                                                                             | Ball screw C7(normal) |      |     |
| 200                   | 532  | 1 | 11.3        | Lead                                                                                                                    | mm                                                                                                                                                          | 10                    | 20   |     |
| 300                   | 632  | 2 | 12.3        | Rated RPM                                                                                                               | RPM                                                                                                                                                         | 3000                  | 3000 |     |
| 400                   | 732  | 2 | 13.3        | Max linear speed*                                                                                                       | mm/sec                                                                                                                                                      | 500                   | 1000 |     |
| 500                   | 832  | 3 | 14.3        | Rated thrust                                                                                                            | N                                                                                                                                                           | 560                   | 280  |     |
| 600                   | 932  | 3 | 15.3        | Repeatability                                                                                                           | mm                                                                                                                                                          | ±0.02                 |      |     |
| 700                   | 1032 | 4 | 16.3        | Effective stroke                                                                                                        | mm                                                                                                                                                          | 200~1200              |      |     |
| 800                   | 1132 | 4 | 17.3        | Max load (H)                                                                                                            | kg                                                                                                                                                          | 110                   | 50   |     |
| 900                   | 1232 | 5 | 18.3        | <div>Rated dynamic load**<br/></div> | Fyd                                                                                                                                                         | N                     | 50   | 50  |
| 1000                  | 1332 | 5 | 19.3        |                                                                                                                         | Fzd                                                                                                                                                         | N                     | 1100 | 500 |
| 1100                  | 1432 | 6 | 20.3        |                                                                                                                         | Mxd                                                                                                                                                         | N-m                   | 60   | 65  |
| 1200                  | 1532 | 6 | 21.3        |                                                                                                                         | Myd                                                                                                                                                         | N-m                   | 45   | 53  |
|                       |      |   |             |                                                                                                                         | Mzd                                                                                                                                                         | N-m                   | 45   | 53  |
|                       |      |   |             | Permitted load condition***                                                                                             | $\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1$ <p>Fy, Fz, Mx, My, Mz are working loads</p> |                       |      |     |

\* Vibration might occur when the effective stroke is longer than 800mm.


The maximum speed should be decreased by 15% for every 100mm of increased stroke.


\*\* The load condition is based on 10,000km operation.

\*\*\* If used on the vertical axis or in a special condition, please contact HIWIN.

## Model Number for KS180B-FL

| KS180 | B           | -120             | C               | -3000            | A              | FL           | S2                                                                                                              | M401                                                                                                                 |
|-------|-------------|------------------|-----------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Timing Belt | Pulley Perimeter | Precision Grade | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       |             |                  | C:<br>Normal    |                  | A:<br>Standard | FL: Left     | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M20□, K20□<br>M40□, K40□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |




| Effective stroke (mm) | L    | N  | Weight (kg) | AC motor output            |                                                                                                                 | W      | 400         |    |
|-----------------------|------|----|-------------|----------------------------|-----------------------------------------------------------------------------------------------------------------|--------|-------------|----|
|                       |      |    |             | Drive                      |                                                                                                                 |        | Timing Belt |    |
| 200                   | 639  | 2  | 14.2        | Pulley Perimeter           |                                                                                                                 | mm     | 120         |    |
| 400                   | 839  | 3  | 17.0        | Pulley RPM                 |                                                                                                                 | RPM    | 900         |    |
| 600                   | 1039 | 4  | 19.8        | Max linear speed           |                                                                                                                 | mm/sec | 1800        |    |
| 800                   | 1239 | 5  | 22.6        | Rated thrust               |                                                                                                                 | N      | 133         |    |
| 1000                  | 1439 | 6  | 25.4        | Repeatability              |                                                                                                                 | mm     | ±0.1        |    |
| 1200                  | 1639 | 7  | 28.2        | Effective stroke           |                                                                                                                 | mm     | 200~3000    |    |
| 1400                  | 1839 | 8  | 31.0        | Max load (H)               |                                                                                                                 | kg     | 30          |    |
| 1600                  | 2039 | 9  | 33.8        | Rated dynamic load*        |                              | Fyd    | N           | 50 |
| 1800                  | 2239 | 10 | 36.6        |                            | Fzd                                                                                                             | N      | 300         |    |
| 2000                  | 2439 | 11 | 39.4        |                            | Mxd                                                                                                             | N-m    | 70          |    |
| 2200                  | 2639 | 12 | 42.2        |                            | Myd                                                                                                             | N-m    | 55          |    |
| 2400                  | 2839 | 13 | 45.0        |                            | Mzd                                                                                                             | N-m    | 55          |    |
| 2600                  | 3039 | 14 | 47.8        | Permitted load condition** | $\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1$ |        |             |    |
| 2800                  | 3239 | 15 | 50.6        |                            | Fy, Fz, Mx, My, Mz are working loads                                                                            |        |             |    |
| 3000                  | 3439 | 16 | 53.4        |                            |                                                                                                                 |        |             |    |


\*The load condition is based on 10,000km operation.

\*\*For horizontal applications only. If used in a special condition, please contact HIWIN.

## Model Number for KS180B-FR

| KS180 | B           | -120             | C               | -3000            | A              | FR           | S2                                                                                                              | M401                                                                                                                 |
|-------|-------------|------------------|-----------------|------------------|----------------|--------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model | Timing Belt | Pulley Perimeter | Precision Grade | Effective Stroke | Slider Type    | Motor Flange | Limit Switch                                                                                                    | Motor                                                                                                                |
|       |             |                  | C:<br>Normal    |                  | A:<br>Standard | FR: Right    | S1: OMRON SX671<br>S2: OMRON SX674<br>S3: Panasonic GX-F12A<br>S4: Panasonic GX-F12A-P<br>None: No Limit Switch | M20□, K20□<br>M40□, K40□<br>Motor specification:<br>ref. catalog P.167<br>M:customer specified<br>None:Without Motor |



| Effective stroke (mm)      | L                                                                                                                                                           | N   | Weight (kg) | AC motor output                                                                                                                                                                                                                                                                                                                                    | W                          | 400                                                                                                                                                         |    |     |   |     |     |     |    |     |     |    |     |     |    |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|----|-----|---|-----|-----|-----|----|-----|-----|----|-----|-----|----|
|                            |                                                                                                                                                             |     |             | Drive                                                                                                                                                                                                                                                                                                                                              |                            | Timing Belt                                                                                                                                                 |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 200                        | 639                                                                                                                                                         | 2   | 14.2        | Pulley Perimeter                                                                                                                                                                                                                                                                                                                                   | mm                         | 120                                                                                                                                                         |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 400                        | 839                                                                                                                                                         | 3   | 17.0        | Pulley RPM                                                                                                                                                                                                                                                                                                                                         | RPM                        | 900                                                                                                                                                         |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 600                        | 1039                                                                                                                                                        | 4   | 19.8        | Max linear speed                                                                                                                                                                                                                                                                                                                                   | mm/sec                     | 1800                                                                                                                                                        |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 800                        | 1239                                                                                                                                                        | 5   | 22.6        | Rated thrust                                                                                                                                                                                                                                                                                                                                       | N                          | 133                                                                                                                                                         |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 1000                       | 1439                                                                                                                                                        | 6   | 25.4        | Repeatability                                                                                                                                                                                                                                                                                                                                      | mm                         | ±0.1                                                                                                                                                        |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 1200                       | 1639                                                                                                                                                        | 7   | 28.2        | Effective stroke                                                                                                                                                                                                                                                                                                                                   | mm                         | 200~3000                                                                                                                                                    |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 1400                       | 1839                                                                                                                                                        | 8   | 31.0        | Max load (H)                                                                                                                                                                                                                                                                                                                                       | kg                         | 30                                                                                                                                                          |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 1600                       | 2039                                                                                                                                                        | 9   | 33.8        | <div></div> <div><table><tr><td>Fyd</td><td>N</td><td>50</td></tr><tr><td>Fzd</td><td>N</td><td>300</td></tr><tr><td>Mxd</td><td>N-m</td><td>70</td></tr><tr><td>Myd</td><td>N-m</td><td>55</td></tr><tr><td>Mzd</td><td>N-m</td><td>55</td></tr></table></div> | Fyd                        | N                                                                                                                                                           | 50 | Fzd | N | 300 | Mxd | N-m | 70 | Myd | N-m | 55 | Mzd | N-m | 55 |
| Fyd                        | N                                                                                                                                                           | 50  |             |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |
| Fzd                        | N                                                                                                                                                           | 300 |             |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |
| Mxd                        | N-m                                                                                                                                                         | 70  |             |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |
| Myd                        | N-m                                                                                                                                                         | 55  |             |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |
| Mzd                        | N-m                                                                                                                                                         | 55  |             |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 1800                       | 2239                                                                                                                                                        | 10  | 36.6        |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 2000                       | 2439                                                                                                                                                        | 11  | 39.4        |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 2200                       | 2639                                                                                                                                                        | 12  | 42.2        |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 2400                       | 2839                                                                                                                                                        | 13  | 45.0        |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 2600                       | 3039                                                                                                                                                        | 14  | 47.8        | <div><table><tr><td>Permitted load condition**</td><td colspan="3"><math display="block">\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1</math><p>Fy, Fz, Mx, My, Mz are working loads</p></td></tr></table></div>                                                                   | Permitted load condition** | $\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1$ <p>Fy, Fz, Mx, My, Mz are working loads</p> |    |     |   |     |     |     |    |     |     |    |     |     |    |
| Permitted load condition** | $\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1$ <p>Fy, Fz, Mx, My, Mz are working loads</p> |     |             |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 2800                       | 3239                                                                                                                                                        | 15  | 50.6        |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |
| 3000                       | 3439                                                                                                                                                        | 16  | 53.4        |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |
|                            |                                                                                                                                                             |     |             |                                                                                                                                                                                                                                                                                                                                                    |                            |                                                                                                                                                             |    |     |   |     |     |     |    |     |     |    |     |     |    |


\*The load condition is based on 10,000km operation.

\*\*For horizontal applications only. If used in a special condition, please contact HIWIN.

## 6.4 Motor Adaptor Flange List


### KS90

Motor Adaptor Flange F0




### KS120


Motor Adaptor Flange FI



Motor Adaptor Flange F1




Motor Adaptor Flange FI




### KS100

Motor Adaptor Flange FI




### KS150

Motor Adaptor Flange FI



Motor Adaptor Flange F1



### KS180

Motor Adaptor Flange FI

