


# SUPPORT UNIT : FF SERIES



## SUPPORT UNIT FOR BALL SCREW (GENERAL LOAD)


### FF6 ~ FF30




### Dimensions

Model	Sizes (mm)											Mass (g)	Snap-ring	Bearing
	Body													
	d1	L	H	F	D	A	P.C.D	□B	X	Y	Z			
FF6/FF8	6	10	6	4	22	36	28	28	3.4	6.5	3	30	C6	606ZZ
FF10	8	12	7	5	28	43	35	35	3.4	6.5	4	60	C8	608ZZ
FF12	10	15	7	8	34	52	42	42	4.5	8	4	100	C10	6000ZZ
FF15	15	17	9	8	40	63	50	52	5.5	9.5	5.5	140	C15	6002ZZ
FF17	17	20	11	9	50	77	62	61	6.6	11	6.5	290	C17	6203ZZ
FF20	20	20	11	9	57	85	70	68	6.6	11	6.5	380	C20	6204ZZ
FF25	25	24	14	10	63	98	80	79	9	14	8.5	590	C25	6205ZZ
FF30	30	27	18	9	75	117	95	93	11	17.5	11	930	C30	6206ZZ

### FF25D, FF30D



### FF35, FF40



### Dimensions

Model	Sizes (mm)											Mass (g)	Snap-ring	Bearing
	Body													
	d1	L	H	F	D	A	P.C.D	□B	X	Y	Z			
FF25D	25	30	15	15	80	122	100	92	11	18	11	1400	C25	6205ZZ
FF30D	30	32	15	17	90	138	116	106	11	18	11	1800	C30	6206ZZ
FF35	35	34	15	19	100	154	132	120	11	17.5	11	2050	C35	6207ZZ
FF40	40	36	18	18	120	176	150	128	14	20	13	3050	C40	6208ZZ